

PUNATI CHEMICAL CORP.
MATERIAL SAFETY DATA SHEET

SECTION I

| | | | |
|---|--------------------------------|--|-------------------------------|
| PRODUCT NAME OR NUMBER (as it appears on label) Smells Begone Odor Absorber | | COMMON CODE NA (Not Applicable) | |
| MANUFACTURER'S NAME Punati Chemical Corp. | | EMERGENCY TELEPHONE NO. Punati Chemical 248-276-0101 FAX 248-276-0103 | |
| ADDRESS (Number, City, State and Zip Code) 1160 N. Opdyke Rd. Auburn Hills, MI 48326 | | MANUFACTURER'S NO. NA | |
| HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. (49 CFR 172-101) Non-Hazardous | | | |
| ADDITIONAL HAZARD CLASSES (as applicable) NA | | PREPARED BY Lou Calabris | TITLE General Mgr. |
| CHEMICAL FAMILY Fatty Acid | FORMULA Proprietary Mixture | EFFECTIVE DATE 1/1/2006 | REVISION NO. REVISION DATE |

SECTION II-INGREDIENTS

| CAS REGISTRY NO. | %WT | Chemical Ingredients | Exposure Limits (ppm) | | | OSHA | Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify) |
|------------------|-----|--------------------------------|-----------------------|------|-----|------|---|
| | | | ACGIH TWA | STEL | TWA | | |
| | | | | | | | |
| | | NON-HAZARDOUS INGREDIENTS ONLY | | | | | |
| | | | | | | | |
| | | | | | | | |

SECTION III-PHYSICAL DATA

| | | |
|---|---------------------------------------|-----------------------------------|
| BOILING POINT 185-190°F | SPECIFIC GRAVITY (H20=1) 0.99 | MELTING POINT 120°F |
| VAPOR PRESSURE Vapor as Water | PERCENT VOLATILE BY VOLUME (%) N/A | PERCENT SOLIDS BY WEIGHT 10-16 |
| VAPOR DENSITY (AIR=1) Vapor as Water | EVAPORATION RATE (=1) N/A | |
| SOLUBILITY IN WATER Partially Solid | pH= 8.5 | |
| APPEARANCE AND ODOR Scarlet solid with pleasant odor | MATERIAL TYPE: Solid | |

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

| | | | | |
|--|-------------------|------------------|------------|------------|
| FLASH POINT 200°F | Method Used CC | FLAMMABLE LIMITS | LEL N/A | UEL N/A |
| EXTINGUISHING MEDIA Carbon Dioxide, Foam, Dry Chemicals | | | | |
| SPECIAL FIRE FIGHTING PROCEDURES Wear positive-pressure self-contained breathing apparatus (SCBA) and protective clothing in fire conditions. | | | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS When dry product burns, water, carbon dioxide, carbon monoxide, and smoke are produced. | | | | |

SECTION V-HEALTH HAZARD DATA

| | | |
|--|---|----------------------------------|
| EFFECTS OF OVEREXPOSURE-Conditions to Avoid May cause mild eye irritation | THRESHOLD LIMIT VALUE PERMISSIBLE EXPOSURE LIMIT | See Section II See Section II |
| APPROPRIATE EXPOSURE GUIDELINES Not Established | MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE None Known | |
| PRIMARY ROUTES OF ENTRY Inhalation _____ Skin Contact <u>xx</u> Other (specify) _____ | | |
| EMERGENCY AND FIRST AID PROCEDURES Eye - Flush eye(s) with continuous flow of water for at least 15-minutes. Seek medical assistance if irritation persists. Skin - Wash affected area(s) thoroughly with soap and water. Consult a physician if irritation develops. Ingestion - If swallowed, seek immediate medical attention. | | |

SECTION VI-REACTIVITY DATA

| | | |
|--|---|-----------------------------------|
| STABILITY UNSTABLE STABLE XX | CONDITIONS TO AVOID Excessive heat and open flame | |
| | INCOMPATIBILITY (materials to avoid) Strong oxidizing agents, strong acids, and bases. | |
| HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition may yield carbon monoxide, carbon dioxide. | | |
| HAZARDOUS POLYMERIZATION | MAY OCCUR WILL NOT OCCUR | Conditions to Avoid None Known |
| | XX | |

SECTION VII-SPILL OR LEAK PROCEDURE

| | | |
|---|--|--|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED If liquid: Contain spill. Absorb on sorbant media and place in appropriately labeled waste containers. Residue may be washed with warm water. | | |
| WASTE DISPOSAL METHOD Dispose of waste material in accordance with local, state and federal regulations. | | |
| CERCLA (Superfund) REPORTABLE QUANTITY (lb.) N/A | | |
| RCRA HAZARDOUS WATE NO. (40 CFR 261.33) N/A | | |
| NFPA RATINGS Not Determined | | |

SECTION VIII-SPECIAL PROTECTION INFORMATION

| | | |
|--|---|-----------------|
| RESPIRATORY PROTECTION (specify type) Melted State: Not required under normal conditions in a well-ventilated workspace. If ventilation is inadequate for high vapor concentrations, a respirator with an organic vapor cartridge is recommended. | | |
| Ventilation | LOCAL EXHAUST (Specify Rate) Recommended | SPECIAL None |
| | MECHANICAL (General) (Specify Rate) Fan | OTHER |
| PROTECTIVE GLOVES (Specify type) None | EYE PROTECTION (Specify type) None | |
| OTHER PROTECTIVE EQUIPMENT Apron (at risk of splash), eye wash. | | |

SECTION IX-SPECIAL PRECAUTIONS

| | | |
|--|--|--|
| PRECAUTION TO BE TAKEN IN HANDLING AND STORING Store product at moderate temperatures, 40°F-90°F. | | |
| OTHER PRECAUTIONS Store in a cool place. | Keep away from children. Contents may liquify in temperatures above 120°F. Will resolidify without impairing efficiency of product. | Keep plastic containers away from open flames. |

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Punati Chemical Corp.
The data on this sheet relates only to the specific material designed therein. Punati Chemical Corp. assumes no legal responsibility for use or reliance upon this date.